

---

---

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-294143

(43)Date of publication of application : 26.10.1999

(51)Int.Cl.

F01N 3/08

B01D 53/18

B01D 53/60

B01D 53/77

F01N 3/02

(21)Application number : 10-101190

(71)Applicant : SAKAKIBARA AKIRA

(22)Date of filing : 13.04.1998


(72)Inventor : SAKAKIBARA AKIRA

## (54) EXHAUST EMISSION CONTROL DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To possibly reduce poisonous material contained in exhaust gas discharged from an internal combustion engine.

SOLUTION: Wall portions 4 are arranged in an intermediate portion of a cylindrical pipe 2. A number of tubular nozzles 5 are fixed so as to penetrate the wall portions 4. An upstream side U of the cylindrical pipe 2 is connected to an exhaust pipe 1 arranged continuously from an internal combustion engine, while an exhaust port 6 is formed on a front of a downstream side D of the cylindrical pipe 2. In addition, a communication pipe 8 having an air suctioner 7 is connected. A liquefied material sedimentation part 9 is arranged on a lower portion of the cylindrical pipe 2 on the downstream side D. In such a case, the exhaust gas fed into the cylindrical pipe 2 on the upstream side U is flowed down into the cylindrical pipe 2 on the downstream side D in which pressure is reduced by the air suctioner 7. At this time, moisture contained in the exhaust gas is speedily cooled and condensed. Poisonous material contained in the exhaust gas is mixed therein for sedimentation. The purified exhaust gas is discharged to the outside from the exhaust port 6.



## LEGAL STATUS

[Date of request for examination] 16.06.1999

[Date of sending the examiner's decision of rejection] 13.08.2002

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3366249

[Date of registration] 01.11.2002

[Number of appeal against examiner's decision of rejection] 2002-16087

[Date of requesting appeal against examiner's decision of rejection] 22.08.2002

[Date of extinction of right]